



F-500 EA[®] FIRE EXTINGUISHER

Powered by
HCT's Fluorine-Free
Encapsulator Technology

Engineered Advantage

The F-500 EA[®] Fire Extinguisher provides unmatched incipient fire protection and flammable spill control in a small package. This stainless steel unit is effective on a variety of hazards, including polar and non-polar fuels. A single charge can encapsulate a half-gallon spill in minutes.



Nominal Measurements

Capacity	9.5 L (2.5 G)
Dimensions	571.5 X 178 MM (22.5 X 7 IN)
Weight	3.4 KGS (7.5 LBS)
Flow Time	45 SEC
Working Pressure	10 BAR (150 PSI)

Hazard Control Technologies, Inc.

150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM

APPLICATIONS

Class A Hazards
Common Materials

MN
SB

Class B Hazards
Flammable Liquids

MN
SB

Class D Hazards
Combustible Metals

MN

Class K Hazards
Oils and Fats

MN

Lithium-ion Hazards
Rechargeable Devices

MN
SB

Firefighting



Fire Protection



Select an Assembly

Misting Nozzle (MN)
Straight Bore (SB)

For unmatched versatility,
we recommend our Misting Nozzle (MN),
and for expert Class A applications
that demand a greater distance,
our Straight Bore (SB) is ideal.

How to Order

Part # F5 FE 9.7L-SS-NB-MN

Part # F5 FE 9.7L-SS-NB-SB

The F-500 EA® Fire Extinguisher is
sold unfilled. F-500 EA® Recharge
Kits are sold separately. For refilling
F-500 EA® Fire Extinguishers in bulk,
use a 5-gallon pail of F-500 EA®.

Hazard Control Technologies, Inc.

150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM